

HALO Smart Sensor is Patented.

HALO Smart Sensor

our all-in-one health, safety and vape device.

monitoring Carbon Dioxide (CO2), Particulate Concentrations, Humidity, Volatile Organic Compounds (VOC), and Nitrogen Dioxide (NO2) in the air. HALO delivers safe, healthy, and comfortable environments that keeps all personnel safe while, at the same time, saving money by efficiently running the HVAC system.



GUNSHOT DETECTION

Add an extra layer of protection with HALO. Identify gunshots and the location with two-factor authentication. This sensor is 3rd party certified.



AGGRESSION DETECTION

Protect your staff and customers. With HALO you are able to detect fights and loud noises in usually quiet areas.



HELP (SPOKEN KEY WORD)

Staff and customers can call for help using specific keywords. Whenever the keyword is said aloud, HALO will send notifications to those who have been designated to receive these alerts.



AIR QUALITY MONITORING

Automate and ensure proper ventilation in each room with BACnet integration.



VAPE AND MARIJUANA (THC) DETECTION

Identify vaping in privacy areas such as bathrooms, break rooms, and the sales floor.



PREVENT SPREAD OF INFECTIOUS **DISEASE**

Ensure rooms have been cleaned and that air is properly filtered.



CUSTOM: VANDALISM & TRESPASSING

Receive notifications when lights or noise is detected in unauthorized areas and after hours.



CUSTOM: MANAGE HVAC ENERGY

Monitor HVAC effectiveness and only use when rooms are occupied.



Key Features





















Health Index

Air Quality Index

Carbon Monoxide

Carbon Dioxide

Nitrogen Dioxide

Relative Humidity

Temperature

Particulates

Help

















(Spoken Keyword)

Gunshot

Aggression

Light Level

Vape

Vape Masking

General Specifications

Operating Temperature	32°F - 122°F (0°C - 50°C)	
Operating Humidity	0 to 90% Relative Humidity (non-condensing)	
Power Supply	PoE (IEEE 802.3af Class 3 Compliance) 9W	
Dimensions	5.75" x 3.08" (146mm x 78mm)	
Weight	0.8 lbs (0.365 kgs)	
Mounting Options	options Ceiling Flush Mount, Surface Mount (optional)	
Vandal	IK10 rated, vandal proof housing with Tamper Alert	
Certifications	UL, CUL, CE, RoHS, FCC, WEEE, California IoT Security 1798.91.04, C-Tick and CRM Compliant	

Network Specifications

Ethernet	RJ-45 (10/100 Base-T)
Alarm Triggers	Air Quality Index (AQI), Health Index, Vape, Vape THC, Aggression, Gunshot, Spoken Key Word, Tamper, Particulates, Carbon Dioxide Equivalents, Total Volatile Organic Compounds, Carbon Monoxide, Ammonia, Temperature/Humidity, Light Level, Sound Levels, Building Health
Protocols	BACnet, RTSP, TCP/IP, UDP, IPV4/V6, HTTP, HTTPS, DHCP, ARP, Bonjour, Wireless Connectivity
Maximum User Connections	Live MJPEG Stream, 8 Users

Interface Specifications

*Image display of sensor readings only.

Live Display Resolution*	1024 x 768
Frame Rate*	1 FPS
Audio	MEMS Microphones (2) [Audio Analysis Only] No Recording of Live Stream
Relays Outputs	2, Normally Open or Closed, 48VDC at 1 amp
Status Light	Alarm Condition, Multi-Color, Programmable
Speaker	Alarm Condition, Pre-Recorded Files, Programmable WAV Files

Connect to HALO Cloud to manage multiple devices, receive real-time Health Index and AQI alerts and reporting, see alerts and historical data to document your buildings health status and trouble areas.

VMS Integrations: Milestone, Genetec, Avigilon, ExacQ Vision, Rhombus Systems, Arcules, Vivotek, Pelco, Ganz Cortrol, Nx Witness, Qognify, DW Spectrum IPVMS, Mirasys, Video Insight, EoCortex, Wisenet Wave VMS, Axxonsoft, Digifort, and many others!

Supported Languages: English, Foreign Languages Supported



Other 3rd Party Integrations: The Boring Lab, Presence Management, IDentifyED, Vigilance Software, Punch Alert, DIR-S, Extreme Network Defender, Aruba HPE, Connect One, AMT, Audio Enhancement, Gallagher, NuLEDs, Singlewire Informacast and many others!

Emergency Key Words: HALO supports multiple key words

