Vape and THC

Chemical and Gas

Manage Energy Costs





HALO Smart Sensor

shot Detection

our all-in-one health, safety and vape device.

HALO is a key component in the solution to providing a low-risk environment by monitoring Carbon Dioxide (CO2), Particulate Concentrations, Humidity, Volatile Organic Compounds (VOC), and Nitrogen Dioxide (NO2) in the air. **HALO** delivers safe, healthy, and comfortable environments that keeps all personnel safe while, at the same time, saving money by efficiently running the HVAC system.



DISEASE PREVENTION

Ensure your residents and staff are safe from airborne diseases, prevent the spread of infectious disease, ensure rooms have been cleaned, and the air is properly filtered.



VAPE AND MARIJUANA (THC) DETECTION

Identify vaping and THC usage in privacy areas such as resident rooms, bathrooms, break rooms, and common areas.



GUNSHOT DETECTION

Add an extra layer of protection with HALO. Identify gunshots and the location with two-factor authentication. This sensor is 3rd party certified.



CUSTOM: VANDALISM & TRESPASSING

Receive notifications when lights or noise is detected in unauthorized areas and after hours.



AIR QUALITY MONITORING

See the average quality of the air you are breathing over the course of a few hours. Automate and ensure proper ventilation in each room with BACnet integration.



CHEMICAL AND GAS DETECTION

Catch chemical spills and hazardous gases in mechanical or utility rooms, custodial closets, and maintenance areas.



AGGRESSION DETECTION

Protect your staff and residents. With HALO you are able to detect fights and loud noises in usually quiet areas.



CUSTOM: MANAGE HVAC ENERGY COSTS

Monitor HVAC effectiveness and only use when rooms are occupied.



Key Features





















Health Index

Air Quality Index

Carbon Monoxide

Carbon Dioxide

Nitrogen Dioxide

Relative Humidity

Temperature

Particulates

Help

















(Spoken Keyword)

Gunshot

Aggression

Light Level

Tamper

Vape

Vape Masking

General Specifications

| Operating Temperature | 32°F - 122°F (0°C - 50°C) |
|-----------------------|--|
| Operating Humidity | 0 to 90% Relative Humidity (non-condensing) |
| Power Supply | PoE (IEEE 802.3af Class 3 Compliance) 9W |
| Dimensions | 5.75" x 3.08" (146mm x 78mm) |
| Weight | 0.8 lbs (0.365 kgs) |
| Mounting Options | Ceiling Flush Mount, Surface Mount (optional) |
| Vandal | IK10 rated, vandal proof housing with Tamper Alert |
| Certifications | UL, CUL, CE, RoHS, FCC, WEEE, California IoT Security 1798.91.04, C-Tick and CRM Compliant |
| | |

Network Specifications

| Ethernet | RJ-45 (10/100 Base-T) |
|--------------------------|---|
| Alarm Triggers | Air Quality Index (AQI), Health Index, Vape, Vape THC, Aggression, Gunshot, Spoken Key Word, Tamper, Particulates, Carbon Dioxide Equivalents, Total Volatile Organic Compounds, Carbon Monoxide, Ammonia, Temperature/Humidity, Light Level, Sound Levels, Building Health |
| Protocols | BACnet, RTSP, TCP/IP, UDP, IPV4/V6, HTTP, HTTPS, DHCP, ARP, Bonjour, Wireless Connectivity |
| Maximum User Connections | Live MJPEG Stream, 8 Users |

Interface Specifications

*Image display of sensor readings only.

| Live Display Resolution* | 1024 x 768 |
|--------------------------|--|
| Frame Rate* | 1 FPS |
| Audio | MEMS Microphones (2) [Audio Analysis Only] No Recording of Live Stream |
| Relays Outputs | 2, Normally Open or Closed, 48VDC at 1 amp |
| Status Light | Alarm Condition, Multi-Color, Programmable |
| Speaker | Alarm Condition, Pre-Recorded Files, Programmable WAV Files |
| | |
| | |

Connect to HALO Cloud to manage multiple devices, receive real-time Health Index and AQI alerts and reporting, see alerts and historical data to document your buildings health status and trouble areas.

VMS Integrations: Milestone, Genetec, Avigilon, ExacQ Vision, Rhombus Systems, Arcules, Vivotek, Pelco, Ganz Cortrol, Nx Witness, Qognify, DW Spectrum IPVMS, Mirasys, Video Insight, EoCortex, Wisenet Wave VMS, Axxonsoft, Digifort, and many others!

Supported Languages: English, Foreign Languages Supported



2773 21 5 5 4 4 4 3

277 73 21 5 5 4 4 4 3

Emergency Key Words: HALO supports multiple key words

